

BEACON ADHESIVES COMPANY, INC.

Safety Data Sheet 29 CFR 1910.1200



Section 1: Company and Product Identification

Product Name: Liquid Thread

Product Code: Liquid Thread

Company: Beacon Adhesives Company, Inc.
125 MacQuesten Parkway South
Mount Vernon, NY 10550
PH: 914-699-3400

Emergency Response: Chem-Trec 1-800-424-9300

Section 2: Hazards Identification

GHS02

GHS05

GHS08

BLANK

Hazard Pictograms:

Signal Word: Not Applicable

Hazard Category: Non Hazardous

Hazard Statements: Non-Hazardous

Precautionary Statements:

P264: Wash thoroughly after handling
P280: Wear protective gloves/protective clothing/eye protection/face protection
P308+313: IF exposed or concerned: Get medical advice/attention

P501: Dispose of contents/container in accordance with local/national/international rules.

Hazards not otherwise classified: Not applicable, none known.

Section 3: Composition / Information on Ingredients

Hazardous substance (name)	Hazard Category	CAS#	Weight %
Polyvinyl Acetate Emulsion	Non-Hazardous	Prop	>50
Phthalate Ester	Non-Hazardous	Prop	>30
Vinyl Polymer	Non-Hazardous	Prop	>20

Section 4: First Aid Measures

General Info: Product may give off vapors in appreciable quantities affecting the inhalation route. Ensure proper ventilation.

BEACON ADHESIVES COMPANY, INC.

Notable Exposure symptoms: Treat Symptomatically

If ingested: Rinse mouth. Seek immediate medical attention.

If inhaled: Remove to fresh air. Obtain medical attention if asthma-like symptoms or other symptoms develop.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do. Get medical attention if irritation develops or persists.

Skin contact: Take off immediately all contaminated clothing. Rinse with water thoroughly. Get medical advice if irritation develops or persists.

Additional Info: Observe for any symptoms for several hours after exposure. Follow up with medical attention if symptoms develop.

Section 5: Fire Fighting Measures

General Info: None Known

Extinguishing Method / Equipment: Water Spray, Dry chemical, Carbon Dioxide Foam.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and procedures: Wear appropriate personal protective equipment.

Containment Equipment and Procedures: Large Spills: Contain actively spilling material if safe and easy to do so. Dike the spilled material, where this is possible. Utilize absorbent clay or sand to contain and stop spreading material.

Small Spills: Utilize absorbent clay or sand and transfer to waste receptacles.

Cleanup Procedures: Collect all contaminated clay, media, or other cleanup materials into a waste receptacle. If cleaning surface is necessary, utilize mineral spirits or other solvents, provided adequate ventilation is available.

Section 7: Handling and Storage

Safe Handling Precautions: No special precautions are necessary beyond normal good hygiene practices.

Recommendations for Storage: Keep container closed

Section 8: Exposure Control / Personal Protection

BEACON ADHESIVES COMPANY, INC.

General / Local exhaust ventilation should be utilized. Eye wash facilities must be available when handling Engineering this product.

Controls:

Work Clothing: Protective work clothing which covers skin and prevents exposures.

Eye/face protection: Wear safety goggles or face shield.

Skin Protection: Use good hygiene.

Respiratory Utilize respirator if airborne levels are not maintained below exposure limits, or if ventilation is Protection: inadequate.

Additional Observe good chemical hygiene practices. Do not smoke or eat while using this product. Wash Information: hands or exposed skin after using the product.

Section 9: Physical and Chemical Properties

State: Liquid	Melting Point: N/A	Freezing Point: 32 F
Color: White	Boiling Point/Range: 212 F	pH N/A
Sp Grav: 1.1 1.2	Odor: N/A	
	Flash Point: N/A	
Upper Flam Limits: Not avail	Lower Flam Limits: Not avail	
	Viscosity: 800 cSt	

Section 10: Stability and Reactivity

General: This product is stable.

Conditions to avoid Freezing Temperatures.

Section 11: Toxicological Information

General Information: N/A

Toxicological Product has not been tested. Solvent vapors may cause drowsiness or dizziness. Prolonged Information inhalation may be harmful to human health. Irritating in case of skin or eye contact. May be (product): harmful if swallowed or in contact with skin.

Likely Routes of Exposure: Inhalation of vapors, dermal

BEACON ADHESIVES COMPANY, INC.

Toxicological Information (contained substances)

Hazardous substance (name)	LD50 Oral	LD50 Dermal	LC50 Inh	Irritancy:
Polyvinyl Acetate Emulsion	No Info	No Info	No Info	None
Phthalate Esters	No Info	No Info	No Info	None

Section 12: Ecological Information

General information: Product not Hazardous

Aquatic toxicity: N/A

Degradation / Mobility info: N/A

Bioaccumulative potential: N/A

Section 13: Disposal Information

Product disposal: Dispose of product in accordance with local, regional, and national regulations. Consult with waste contractor. Contains low levels of flammable solvents.

Container disposal: Treat empty containers with extra care, Recommending crushing containers.

Other considerations: No further information.

Section 14: Transport Information

DOT: Non-regulated

IMO/IMDG: Non-regulated

IATA: Non-regulated

OTHER: Inquire for further transport information.

Comments:

Section 15: Regulatory Information

TSCA: Not Listed

CERCLA RQ: Unlisted

SARA 311/312: Not Listed

SARA 313 Not Listed

Section 16: Other Information

SDS Author: Pete Ryan

Version Date: 5/12/2020

BEACON ADHESIVES COMPANY, INC.

The information accumulated herein is based on data which Beacon Chemical Co., Inc. considers to be accurate; provided however, that the company makes no warranty as to the accuracy of the data. Anyone intending to use the information contained herein shall assume sole and complete responsibility for the results of said use including loss or damage resulting from the handling of the material (COMPANY DISCLAIMER...)